



# Model No. 4T-PCS

## Pull For Help Shower Station

### DESCRIPTION:

The 4T-PCS is a pull cord shower station that is intended for use inside of shower stalls. This station would be located adjacent to the shower head at the same or higher elevation. This places the unit inside the stall but not exposed to a direct stream of water.

The station includes a rubber gasket which provides a seal between the faceplate and the smooth wall surface. If walls are uneven, such as in a tiled shower stall, additional caulking may be required. Mounting screws are provided with rubber O-rings to help keep moisture out.

The front panel has a scratch resistant Lexan® overlay. The overlay reads "PULL FOR HELP" in both English and *Spanish* in bold easy to read red lettering. A red flashing call assurance LED is viewable when activated.

The station is activated by means of a pull down locking toggle switch. It is provided with a 6' long special PVC coated cord with a bright red solid plastic pendant on the lower end. The cord is designed in this fashion so that it will not soak up bodily fluids or other liquids that can transmit infections to staff or patients. It is also easily wiped down with disinfectant for cleaning. At the time of installation the cord shall be adjusted so that the red pendant hangs within 12" above the finished floor.

When the cord is pulled the call will illuminate in four locations simultaneously. The call assurance indicator will flash red, the corridor dome and/or zone lights will flash white or red as specified, the enunciator panel at the nurses' station will show a priority level call LED and a room indicator will flash. In addition a priority level call tone will sound at the nurses' station. A priority level LED and call tone will also sound from any associated duty stations.

The call must be reset at the point of origin by lifting upward on the switch.

### OPTIONAL ACCESSORIES:

B09060-08 Pigtail Connector\*

B09050-08 Pigtail Connector\*

\*Refer to 4T-PCS Wiring Diagram for additional info.



### FEATURES:

- Water resistant
- Durable faceplate
- Cord relief carrier for positive downward pressure from any angle
- Plug-in wiring header for easy removal
- Scratch resistant Lexan® overlay with highly visible nomenclature in English & Spanish
- Call assurance indicator

### SPECIFICATIONS:

**Switch:** Bushings protect the switch against water and dust. Field wiring connections to PCB with insulation displacement connectors.

**Back Box:** Single gang 2-1/2" deep. Steel City #CD or equal.

**Dimensions:** 4.50"H x 2.75"W

**Hardware:** Includes stainless steel mounting screws with rubber O-ring seals.

**Faceplate:** Constructed of UL94V-0 ABS flame resistant plastic.